

# Drop

## Display for wall integration





Brushed stainless steel



Aluminium



APPER HOLM

### **FEATURES**

- In- wall installation
- Brushed stainless steel/ Aluminium/ Glass front frame (depending on the model)
- Easy to install

- · Security anti-theft locking system
- Maintenance free
- HDCP compliant
- Energy saving design

#### GENERAL

Drop monitors have been designed for an easy in-wall installation. They are supplied with a separate box for fix mounting, while the screen itself provides a "clip-on front" system.

They are available with glass, brushed stainless steel and aluminium frames and provide options such as embedded PC, built-in camera and also with touch screen. All models are provided with a galvanised mounting box and are available in a variety of sizes, from 10" to 22".

#### **TECHNICAL SPECIFICATIONS**

#### Display

| Size                            | 15.6" TFT Active Matrix, widescreen   |
|---------------------------------|---|
| Resolution                      | 1366 (h) x 768 (v)  |
| Brightness                      | 300 cd/m2   |
| Contrast ratio                  | 500:1   |
| Pixel                           | 0.252 (h) x 0.252 (v) mm  |
| Viewing angle                   | 80°/80° (u/d) / 85°/85° (l/r)   |
| Viewing area                    | 344.232 (h) x 193.536 (v) mm  |
| LED backlight lifespan          | 50.000 hrs  |
| Response time                   | Tr 6 ms, Tf 2 ms  |
| Temperature (operating/storage) | Operating 0°C - +40°C<br>Storage -20°C - +60°C  |
| Materials                       |   |
| Cabinet                         | Available with front in aluminium (A), stainless steel (I), or glass (G). With mounting box |

## AH15DI/AH15DA/AH15DG Wide

#### Connectivity

| Input signal                            | DVI-I (1 input) - HDCP Compliant<br>DVI-D (1 input) - HDCP Compliant |
|---|--|
| Electrical                              |  |
| Loww voltage<br>(external power supply) | 100-240Vac, 50/60Hz, 12Vdc   |
| Power consumption                       | 50W  |
| Mechanical                              |  |
| Dimensions                              | 422 x 271.50 x 73.50 mm<br>[16.61"x10.69"x2.89"]                     |
| Weight                                  | 4.1 Kg / 9 lbs (Stainless Steel & Aluminium)                         |
|   | 4.6 Kg / 10.1 lbs (Glass)  |
| Shipping Dimensions:                    |  |
| Weight                                  | 5.1 Kg / 11.2 lbs (Stainless Steel & Aluminium)                      |
|   | 5.6 Kg / 12.3 lbs (Glass)  |
| Shipping Box                            | 480 x 380 x 160 mm   |

#### **OPTIONS**

- Touch screen
- Integrated industrial PC
- RS-232 remote control
- HD-BaseT for Video and Power over a single Cat5 cable


#### **CERTIFICATIONS**

CE

#### WARRANTY

• 2 years general warranty

### CONNECTIVITY PANEL



#### CONNECTIVITY

- 1- Power input
- 2- DVI 2 video input
- 3- DVI 1 / DVI A video input

## ARCHITECT'S SPECIFICATIONS

Professional 15.6" widescreen in-wall monitor. Frame available in aluminium, stainless steel or glass. DVI-I and DVI-D connectors. HDCP compliant inputs. Back box with hook system for easy installation. External power supply.

