

DynamicX2

Aluminium retractable motorised monitor







FEATURES

- Automatic 20° inclination
- Passive cover plate
- Front double sided anti-reflective 3mm glass
- Interactive Setup Display
- Maintenance free

- HDCP compliant
- Energy saving design
- Serial control & Remote diagnose
- Individual monitor addressing
- · Integrated terminations switch

GENERAL

DynamicX2 monitors have been designed for installation into tables or desks.

DynamicX2 are elegant monitors built from a solid aluminium block. They have a vertical motorised movement with automatic 20° inclination to ensure the best ergonomics, viewing angle and visibility. This automatic tilting system provides a fast and silent response and highly reliable, maintenance-free solution. DynamicX2 have slightly curved edges for a contemporary and longstanding look. The range is available in Full HD from 15" to 22" and it can be supplied with adjustable tilt, touch screen, camera, single or double retractable microphones, speakers, voting system and multimedia connectors among others.

The anodised aluminium housing can be customised in different colours and finishes. The safety system stops the movement if any resistance is detected for a secure environment.

The standard top-table cover plate is made of brushed stainless steel. It can optionally be supplied with a matt finish or it can disappear when the product is prepared for underneath installation.

DynamicX2 monitors are remotely controllable and diagnosable through the ERT interfaces in an easy and cost effective way.

TECHNICAL SPECIFICATIONS

Display	
Size	FULL HD 17.3" TFT Active Matrix
Resolution	1920 (h) x 1080 (v)
Brightness	400 cd/m2
Contrast ratio	600:1
Pixel	0.1989 (h) x 0.1989 (v) mm
Viewing angle	60°/80° (u/d) / 80°/80° (l/r)
Viewing area	381.888 (h) x 214.812 (v) mm
LED backlight lifespan	50.000 hrs
Response time	Tr 37 ms, Tf 3 ms
Temperature (operating/storage)	Operating 0°C - +40°C Storage -20°C - +60°C
Materials	
Frame	Anodised Aluminium
Glass	AR 2-side with an anti-reflective coating on the glass surface. Thickness: 3.0 ± 0.3 mm
Cover plate	Stainless steel, matt or prepared for underneath installation (to be veneered)
Connectivity	
Input signal	DVI-I (1 input) – HDCP Compliant - Digital / Analog DVI-D (1 input) – HDCP Compliant - Digital

Addressable RS422 monitor control by AHnet protocol

Up/Down control

USB Connector for service

RJ45 CAT5 (with loop)

Contro	ı
Contro	ı

RJ45, RS-422 (I/O)	
Addressing	
Termination switch	
GPI	
IR Remote control (monitor adjustments): 1/5	
Movement's Control	
User interface on monitor	(Up/Down)
Remote	RS-422 I/O/GPI
Electrical	
Low voltage (external power supply)	100-240Vac, 47/63Hz, 12Vdc
Power consumption	50W
Mechanical	
Monitor Dimensions:	
Screen	443 x 258 x 25 mm [17.44"x10.15"x0.98"]
Upper cover plate	540 x 95 x 3 mm [21.26"x3.74"x0.12"]
Housing below the table	525 x 590 x 80 mm [20.67"x23.23"x3.15"]
Weight	19.1 kg / 42.1 lbs
Shipping Dimensions:	
Weight	20.1 kg / 44.3 lbs
Shipping Box	635 x 185 x 725 mm

OPTIONS

GPI (SubD9)

- HDMI/ DynamicLoop
- DynamicShare
- Stainless steel box for keyboard and mouse
- Matte cover plate
- Touch screen
- USB camera
- Composite video camera
- HD-SDI camera
- Built in DynamicTalk
- Motorised retractable synchronised single microphone
- Dual motorised synchronised microphones

CERTIFICATIONS


CE

- USB integrated on cover plate
- 2 USB integrated on cover plate
- USB power integrated on cover plate
- Customised cover plate with speaker, voting system, USB connector
- Prepared for underneath installation, cover plate prepared to be veneered
- Additional Customised laser engraved logotype on the cover plate
- Monitor housing anodised in different colours
- Adjustable tilt

WARRANTY

- 5 years limited warranty
- 2 years general warranty


CONNECTIVITY PANEL



CONNECTIVITY

- 1- AHnet control interface
- 2- USB for Service
- 3- GPI control
- 4- Power input
- 5- DVI 1/ DVI A video input
- 6- DVI 2 video input

INTERACTIVE SETUP DISPLAY



ARCHITECT'S SPECIFICATIONS

Single motor retractable 17.3" Full HD monitor with 20° of automatic inclination. Low voltage. Solid block of aluminium monitor housing in natural anodised finishing, with rounded corners design. Front double sided anti-reflective 3 mm black-edged glass. Passive opening cover plate for enhanced reliability. DVI-I and DVI-D connectors, HDCP compliant inputs.

Easy to read Interactive Set-Up Display (ISD) 2.2" LCD display, allowing local and remote configuration, operation and troubleshooting without having to remove the monitor from the furniture. When connected to the AH ERT interface, the assisted addressing system facilitates the address configuration by simply pressing one button in an easy and convenient way.

Embedded speed and protection pre-sets for quick restore to factory values (enabling a rapid reset to factory values if required). Auto-check feature for auto-diagnostic and internal protection functions. USB port for local firmware upgrade. Safety system that detects obstructions (causing unit to stop).

Adjustable mechanical parameters through AHnet or ISD for calibration and adjustment of mechanics. Adjustable parameters of brightness, contrast and backlight through RS-422. External power supply with 4-Pin XLR4 connector.

