

Drop

Display for wall integration





Brushed stainless steel



Aluminium



AFTERFOLM

FEATURES

- In- wall installation
- Brushed stainless steel/ Aluminium/ Glass front frame (depending on the model)
- Easy to install

- · Security anti-theft locking system
- Maintenance free
- HDCP compliant
- Energy saving design

GENERAL

Drop monitors have been designed for an easy in-wall installation. They are supplied with a separate box for fix mounting, while the screen itself provides a "clip-on front" system.

They are available with glass, brushed stainless steel and aluminium frames and provide options such as embedded PC, built-in camera and also with touch screen. All models are provided with a galvanised mounting box and are available in a variety of sizes, from 10" to 22".

TECHNICAL SPECIFICATIONS

Display

Size	19" TFT Active Matrix, widescreen
Resolution	1440 (h) x 900 (v)
Brightness	250 cd/m2
Contrast ratio	1000:1
Pixel	0.2835 (h) x 0.2835 (v) mm
Viewing angle	80°/80° (u/d) / 85°/85° (l/r)
Viewing area	408.24 (h) x 255.15 (v) mm
LED backlight lifespan	50.000 hrs
Response time	Tr 3.6 ms, Tf 1.4 ms
Temperature (operating/storage)	Operating 0°C — +40°C Storage -20°C — +60°C
Materials	
Cabinet	Available with front in aluminium (A), stainless steel (I), or glass (G). With mounting box

AH19DI/AH19DA/AH19DG Wide

Connectivity

Input signal	DVI-I (1 input) - HDCP Compliant DVI-D (1 input) - HDCP Compliant
Electrical	
Loww voltage (external power supply)	100-240Vac, 50/60Hz, 12Vdc
Power consumption	80W
Mechanical	
Dimensions	488 x 335 x 64.9 mm [19.21"x13.19"x2.56"]
Weight	5.7 Kg / 12.5 lbs (Stainless Steel & Aluminium)
	6.2 Kg / 13.6 lbs (Glass)
Shipping Dimensions:	
Weight	6.7 Kg / 14.7 lbs (Stainless Steel & Aluminium)
	7.2 Kg / 15.8 lbs (Glass)
Shipping Box	550 x 460 x 300 mm

OPTIONS

- Touch screen
- Integrated industrial PC
- RS-232 remote control
- HD-BaseT for Video and Power over a single Cat5 cable


CERTIFICATIONS

CE

WARRANTY

• 2 years general warranty

CONNECTIVITY PANEL



CONNECTIVITY

- 1- Power input
- 2- DVI 2 video input
- 3- DVI 1 / DVI A video input

ARCHITECT'S SPECIFICATIONS

Professional 19" widescreen in-wall monitor. Frame available in aluminium, stainless steel or glass. DVI-I and DVI-D connectors. HDCP compliant inputs. Back box with hook system for easy installation. External power supply.

