Albiral

Universal lift, VESA









GENERAL SPECIFICATIONS

Elegant universal motorised LCD lift with cover plate in brushed stainless steel and rear cover for hiding cables/connectors on the back of the monitors. The ULS lift has a security system for blocked monitors movements. The monitor can be activated using the Up and Down buttons on the cover plate or remotely through RS422 over CAT5 or GPI contact closer. The USL lift has addressing and termination build in, connectivity is done through RJ45 with input and loop through.

The USL does not require any adjustments or fixation to the table or floor, just a cut out in the table surface.

ENGINE

Control UP/DOWN	Buttons on upper cover plate
	GPI contact closer
	RS422 (RJ45 CAT5)

*Optional USB connections in cover plate, not standard

ELECTRICAL	
External power supply	100-240 Vac, 47/63Hz 12Vdc
MECHANICAL	
Dimensions ULS1 mm [inch.]	562x592.5x123.5
	[22.13x23.33x4.86]
Dimensions ULS2	662x592.5x123.5
	[26.06x23.33x4.86]
ACCESSORIES	
ERT	Ethernet interface unit
CHARACTERISTICS	
Universal lift for 15" to 24" monitors	
ULS1	15"-19"
ULS2	19"-24"
Remote control by RS422 & GPI	
Elegant cable/connector cover	
Silent and Reliable	
No adjustments needed	
No fixation to floor	
Customisation available	

Specifications subject to change without previous notice. Albiral is a registered brand by ALBIRAL DISPLAY SOLUTIONS SL

