



**GENERAL SPECIFICATIONS**

LCD type	FULL HD 42.02” TFT Active Matrix, widescreen. LED Backlight
Cabinet	Powder coated

**DISPLAY**

Brightness	700cd/m2
Contrast ratio	4000:1
Resolution (dots)	1920(h) x 1080(v)
Pixel	0.4845 x 0.4845 mm
Viewing angle	89°/89°(u/d) / 89°/89°(l/r)
Viewing area	930.24 x 523.26mm
Response time	Tg-g 8 ms
LED life time (Backlight)	50,000hrs

**INTERNAL INPUTS**

Data inputs	DVI (1 input) HDCP DVI-D (1 input) HDCP
-------------	--

**MECHANICAL**

Total dimension (mm)	2000 x 692 x200
Base dimension(mm)	692 x 557

**POWER**

Power supply	100-240 Vac, 50-60 Hz
Power consumption	280W

**OPTIONS**

TS420	Infrared Touch screen
PG420	Polycarbonate panel protection
NET	RJ 45 connector
AS	Audio and speakers
MB	Mobility wheels
PC	Built in industrial PC
WF	WI-FI
WC	WEBCAM

Specifications subject to change without previous notice. Albiral is a registered brand by ALBIRAL DISPLAY SOLUTIONS SL