



GENERAL SPECIFICATIONS

LCD type	FULL HD 46" TFT Active Matrix, widescreen. LED backlight
Cabinet	Powder coated

DISPLAY

Brightness	700cd/m2
Contrast ratio	4000:1
Resolution (dots)	1920(h) x 1080(v)
Pixel	0.53 x 0.53 mm
Viewing angle	89°/89°(u/d) / 89°/89°(l/r)
Viewing area	1018.08 x 572.67 mm
Response time	Tg-g 6.5 ms
LED life time (Backlight)	50,000hrs

INTERNAL INPUTS

Data inputs	DVIH (1 input) HDCP DVI-D (1 input) HDCP
-------------	---

MECHANICAL

Total dimension (mm)	2000 x 730 x200
Base dimension(mm)	730 x 600

POWER

Power supply	100-240 Vac, 50-60 Hz
Power consumption	320W

OPTIONS

TS460	Infrared Touch screen
PG460	Polycarbonate panel protection
NET	RJ 45 connector
AS	Audio and speakers
MB	Mobility wheels
PC	Built in industrial PC
WF	WI-FI
WC	WEBCAM

Specifications subject to change without previous notice. Albiral is a registered brand by ALBIRAL DISPLAY SOLUTIONS SL