

Albiral

10.4" metal cabinet monitor. Wall mount monitor

Ref: 10WM



GENERAL SPECIFICATIONS

LCD type	10.4" TFT Active Matrix
Cabinet	Powder coated. Wall mount monitor
Controls (*)	Digital

DISPLAY

Brightness	250 cd/m2
Contrast ratio	400:1
Resolution (dots)	800 (h) x 600 (v)
Pixel	0.264 (h) x 0.264 (v) mm
Viewing angle	45°/55° (u/d), 65°/65° (l/r)
Viewing area	211.2 (h) x 158.4 (v) mm
Life lamp	30,000 hrs

OTHER

Response time	Tr 6 ms, Tf 19 ms
Temperature	Operating +0°C ~ +40°C, Storage -20°C ~ +60°C

INPUTS & OUTPUTS (*)

Input signal	DVI-I (1 input) - HDCP Compliant DVI-D (1 input) - HDCP Compliant
--------------	--

ELECTRICAL

External power supply	100-240 Vac, 47/63Hz, 12Vdc
Power consumption	40 W

MECHANICAL

Dimensions	326 x 265 x 71 mm
Weight	4.5 Kg

OPTIONS

PC	Built in industrial PC
WF	Wi-fi network for PC
MPEG	Built in mpeg player. CF player, MPEG1, MPEG2, MPEG4, (PAL/NTSC)
TS10	Touch screen
PG10(**)	Protection polycarbonate

Specifications subject to change without previous notice. Albiral is a registered brand by ALBIRAL DISPLAY SOLUTIONS SL

(*) Not available with PC option

(**) Not available with touch screen option



ALBIRAL DISPLAY SOLUTIONS SL
C/ Fátima 25,
08512 Sant Hipòlit de Voltregà
Barcelona - Spain
Tel.: +34 93 850 23 76 / 23 83
fax: +34 93 850 25 50
web: www.albiral.com
e-mail: marketing@albiral.com

www.albiral.com