

15" metal cabinet monitor. Wall mount monitor**Ref: 15WM****GENERAL SPECIFICATIONS**

LCD type	15" TFT Active Matrix. LED Backlight
Cabinet	Powder coated. Wall mount monitor
Controls (*)	Digital

DISPLAY

Brightness	400 cd/m2
Contrast ratio	700:1
Resolution (dots)	1024 (h) x 768 (v)
Pixel	0.297 (h) x 0.297 (v) mm
Viewing angle	70°/70° (u/d), 80°/80° (l/r)
Viewing area	304.1 (h) x 228.1 (v) mm
LED life time (Backlight)	50,000 hrs

OTHER

Response time	Tr 5 ms, Tf 11 ms
Temperature	Operating +0°C ~ +40°C, Storage -20°C ~ +60°C

INPUTS & OUTPUTS (*)

Input signal	DVI-I (1 input) - HDCP Compliant DVI-D (1 input) - HDCP Compliant
--------------	--

ELECTRICAL

External power supply	100-240 Vac, 47/63Hz, 12Vdc
Power consumption	50 W

MECHANICAL

Dimensions	385 x 309 x 71 mm
Weight	7.5 Kg

OPTIONS

PC	Built in industrial PC
WF	Wi-fi network for PC
MPEG	Built in mpeg player. CF player, MPEG1, MPEG2, MPEG4, (PAL/NTSC)
TS15	Touch screen
PG15 (**)	Protection polycarbonate

Specifications subject to change without previous notice. Albiral is a registered brand by ALBIRAL DISPLAY SOLUTIONS SL

(*) Not available with PC option

(**) Not available with touch screen option