

12.1" widescreen metal cabinet monitor. Wall mount monitor

Ref: 12WM16


GENERAL SPECIFICATIONS

LCD type	12.1" TFT Active Matrix, widescreen format. LED backlight
Cabinet	Powder coated. Wall mount monitor
Controls (*)	Digital

DISPLAY

Brightness	400 cd/m2
Contrast ratio	1000:1
Resolution (dots)	1280 (h) x 800 (v)
Pixel	0.204 (h) x 0.204 (v) mm
Viewing angle	88°/88° (u/d), 88°/88° (l/r)
Viewing area	261.12 (h) x 163.2 (v) mm
LED life time (Backlight)	50,000 hrs

OTHER

Response time	Tr 15 ms, Tf 10 ms
Temperature	Operating +0°C ~ +40°C, Storage -20°C ~ +60°C

INPUTS & OUTPUTS (*)

Input signal	DVI-I (1 input) - HDCP Compliant DVI-D (1 input) - HDCP Compliant
--------------	--

ELECTRICAL

External power supply	100-240 Vac, 47/63Hz, 12Vdc
Power consumption	40 W

MECHANICAL

Dimensions	339 x 241 x 60 mm
Weight	5.8 Kg

OPTIONS

PC	Built in industrial PC
WF	Wi-fi network for PC
MPEG	Built in mpeg player. CF player, MPEG1, MPEG2, MPEG4, (PAL/NTSC)
TS1216	Touch screen
PG12 wide (**)	Protection polycarbonate

Specifications subject to change without previous notice. Albiral is a registered brand by ALBIRAL DISPLAY SOLUTIONS SL

(*) Not available with PC option

(**) Not available with touch screen option



ALBIRAL DISPLAY SOLUTIONS SL
C/ Fàtima 25,
08512 Sant Hipòlit de Voltregà
Barcelona - Spain
Tel.: +34 93 850 23 76 / 23 83
fax: +34 93 850 25 50
web: www.albiral.com
e-mail: marketing@albiral.com

www.albiral.com