


12.1" metal cabinet monitor. Flush wall monitor**Ref: 12FWM****GENERAL SPECIFICATIONS**

LCD type	12.1" TFT Active Matrix. LED backlight
Cabinet	Powder coated. With mounting box
Controls (*)	Digital

DISPLAY

Brightness	400 cd/m2
Contrast ratio	500:1
Resolution (dots)	800 (h) x 600 (v)
Pixel	0.3075 (h) x 0.3075 (v) mm
Viewing angle	50°/60° (u/d), 65°/65° (l/r)
Viewing area	246.0 (h) x 184.5 (v) mm
LED life time (Backlight)	50,000 hrs

OTHER

Response time	Tr 10 ms, Tf 15 ms
Temperature	Operating +0°C ~ +40°C, Storage -20°C ~ +60°C

INPUTS & OUTPUTS (*)

Data input	DVI-I (1 input) DVI-D (1 input)
------------	------------------------------------

ELECTRICAL

External power supply	100-240 Vac, 47/63Hz, 12Vdc
Power consumption	40 W

MECHANICAL

Dimensions	325.5 x 264.5 x 68.5 mm
Weight	6 Kg

OPTIONS

PC	Built in industrial PC
WF	Wi-fi network for PC
MPEG	Built in mpeg player. CF player, MPEG1, MPEG2, MPEG4, (PAL/NTSC)
TS12	Touch screen
PG12 (**)	Protection polycarbonate



Specifications subject to change without previous notice. Albiral is a registered brand by ALBIRAL DISPLAY SOLUTIONS SL

(*) Not available with PC option

(**) Not available with touch screen option