



GENERAL SPECIFICATIONS

LCD type	FULL HD 17.3" TFT Active Matrix. LED backlight
Cabinet	Powder coated. With mounting box
Controls (*)	Digital

DISPLAY

Brightness	400 cd/m2
Contrast ratio	600:1
Resolution (dots)	1920 (h) x 1080 (v)
Pixel	0.1989 (h) x 0.1989 (v) mm
Viewing angle	60°/80° (u/d), 80°/80° (l/r)
Viewing area	381.888 (h) x 214.812 (v) mm
LED life time (Backlight)	50,000 hrs

OTHER

Response time	Tr 37 ms, Tf 3 ms
Temperature	Operating +0°C ~ +40°C, Storage -20°C ~ +60°C

INPUTS & OUTPUTS (*)

Input signal	DVI-I (1 input) - HDCP Compliant DVI-D (1 input) - HDCP Compliant
--------------	----------------------------------------------------------------------

ELECTRICAL

External power supply	100-240 Vac, 47/63Hz, 12Vdc
Power consumption	70 W

MECHANICAL

Dimensions	463 x 296 x 73.5 mm
Weight	8.5 Kg

OPTIONS

PC	Built in industrial PC
WF	Wi-fi network for PC
MPEG	Built in mpeg player. CF player, MPEG1, MPEG2, MPEG4, (PAL/NTSC)
TS170HD	Touch screen
PG17 wide (**)	Protection polycarbonate



Specifications subject to change without previous notice. Albiral is a registered brand by ALBIRAL DISPLAY SOLUTIONS SL

(*) Not available with PC option

(**) Not available with touch screen option