



**GENERAL SPECIFICATIONS**

LCD type	FULL HD 21.5" TFT Active Matrix. LED backlight
Cabinet	Powder coated. With mounting box
Controls (*)	Digital

**DISPLAY**

Brightness	250 cd/m2
Contrast ratio	1000:1
Resolution (dots)	1920 (h) x 1080 (v)
Pixel	0.247 (h) x 0.247 (v) mm
Viewing angle	178° (h), 178° (v)
Viewing area	476.064 (h) x 267.786 (v) mm
LED life time (Backlight)	30,000 hrs

**OTHER**

Response time	Tg-g 25 ms
Temperature	Operating +0°C ~ +40°C, Storage -20°C ~ +60°C

**INPUTS & OUTPUTS (\*)**

Input signal	DVI-H (1 input) - HDCP Compliant DVI-D (1 input) - HDCP Compliant
--------------	--

**ELECTRICAL**

External power supply	100-240 Vac, 47/63Hz, 12Vdc
Power consumption	80 W

**MECHANICAL**

Dimensions	547 x 339.3 x 63.9 mm
Weight	12 Kg

**OPTIONS**

PC	Built in industrial PC
WF	Wi-fi network for PC
MPEG	Built in mpeg player. CF player, MPEG1, MPEG2, MPEG4, (PAL/NTSC)
TS22016	Touch screen
PG22 wide (**)	Protection polycarbonate



Specifications subject to change without previous notice. Albiral is a registered brand by ALBIRAL DISPLAY SOLUTIONS SL

(\*) Not available with PC option

(\*\*) Not available with touch screen option