Albiral

Smart 12.1" painted steel retractable monitor, with 20 degrees of inclination

Ref: ALB12MR



| LCD type | 12.1" TFT Active Matrix. |
|-----------------------|----------------------------------|
| | LED Backlight |
| Upper cover plate | Brushed stainless steel |
| Monitor cabinet | Powder coated |
| Inclinated screen | 20° (factory adjusted) |
| DISPLAY | |
| Brightness | 600cd/m2 |
| Contrast ratio | 700:1 |
| Resolution (dots) | 1024(h) x 768(v) |
| Pixel | 0.240(h) x 0.240(v) mm |
| Viewing angle | 70°/70°(u/d), 80°/80°(l/r) |
| Viewing area | 245.76(h) x 184.32(v) mm |
| LED life time | 50,000 hrs |
| ENGINE | |
| Control UP/DOWN | Buttons on upper cover plate |
| | RS422 (RJ45 CAT5) |
| Electronic control | PWM |
| OTHER | |
| Response time | Tr 5 ms, Tf 11 ms |
| Temperature | Operating +0°C ~ +40°C, |
| | Storage -20°C ~ +60°C |
| Monitor control | RS422 (RJ45 CAT5) |
| ACCESSORIES | |
| ERT | Ethernet interface unit |
| AH mcs | MonitorControl software |
| CONNECTIONS | |
| Input signal | DVI-I (1 input) - HDCP Compliant |
| | DVI-D (1 input) - HDCP Complian |
| RJ45 CAT5 (with loop) | Addressable RS422 monitor |
| | control by AHnet protocol |

| 100-240 Vac, 47/63Hz |
|---|
| 12Vdc-6.67A |
| 40W |
| 1011 |
| Keyboard and mouse storage box |
| Touch screen |
| Built in FULL HD camera with USB |
| connector |
| Composite video built in camera |
| HD SDI camera |
| Built in DynamicTalk |
| Motorised retractable |
| synchronised single microphone |
| Dual motorised synchronised |
| microphones |
| USB connector on cover plate |
| 2 USB connectors on cover plate |
| USB power on cover plate |
| Customised cover plate with |
| speaker, voting system, USB |
| connector |
| Prepared for underneath |
| installation, cover plate to be |
| veneered |
| Additional customised laser |
| engraved logotype on the cover |
| engraved logotype on the cover |
| plate |
| - · · · · · · · · · · · · · · · · · · · |
| |

