

Electrically foldable FULL HD 21.5" painted steel monitor**Ref: ALB22HDMF****GENERAL SPECIFICATIONS**

LCD type	FULL HD 21.5" TFT Active Matrix, widescreen format. LED Backlight
Cabinet	Powder coated

DISPLAY

Brightness	250cd/m2
Contrast ratio	1000:1
Resolution (dots)	1920(h) x 1080(v)
Pixel	0.247(h) x 0.247(v) mm
Viewing angle	178°(v), 178°(h)
Viewing area	476.064(h) x 267.786(v) mm
LED life time	30,000 hrs

ACCESSORIES

ERT	Ethernet interface unit
AH mcs	MonitorControl software

CONNECTIONS

Input signal	DVI-I (1 input) - HDCP Compliant DVI-D (1 input) - HDCP Compliant
RJ45 CAT5 (with loop)	Addressable RS422 monitor control by AHnet protocol
GPI (SubD 9)	Up/down control

ELECTRICAL

External power supply	100-240 Vac, 47/63Hz, 12Vdc
Power consumption	65W

OTHER

Response time	Tg-g 25 ms
Temperature	Operating +0°C ~ +40°C, Storage -20°C ~ +60°C

OTIONS

TS22016	Touch screen
UC	Built in FULL HD camera with USB connector
CVC	Composite video built in camera
HDSDIC	HD SDI camera
DynamicTalk	Built in DynamicTalk
CCUSB	USB connector on cover plate
CC2USB	2 USB connectors on cover plate
CCUSBPower	USB power on cover plate

Specifications subject to change without previous notice. Albiral is a registered brand by ALBIRAL DISPLAY SOLUTIONS SL