

Electrically foldable 12.1" painted steel monitor with horizontal movement**Ref: ALB12WMFH****GENERAL SPECIFICATIONS**

LCD type	12.1" TFT Active Matrix. LED Backlight
Cabinet	Powder coated
Controls	Digital

DISPLAY

Brightness	600cd/m2
Contrast ratio	700:1
Resolution (dots)	1024(h) x 768(v)
Pixel	0.240(h) x 0.240(v) mm
Viewing angle	70°/70°(u/d), 80°/80°(l/r)
Viewing area	245.76(h) x 184.32(v) mm
LED life time	50,000 hrs

ACCESSORIES

ERT	Ethernet interface unit
AH mcs	MonitorControl software

CONNECTIONS

Input signal	DVI-I (1 input) - HDCP Compliant DVI-D (1 input) - HDCP Compliant
RJ45 CAT5 (with loop)	Addressable RS422 monitor control by AHnet protocol
GPI (SubD 9)	Up/down control

ELECTRICAL

External power supply	100-240 Vac, 47/63Hz, 12Vdc
Power consumption	50W

OTHER

Response time	Tr 5 ms, Tf 11 ms
Temperature	Operating +0°C ~ +40°C, Storage -20°C ~ +60°C

OPTIONS

TS12016	Touch screen
UC	Built in FULL HD camera with USB connector
CVC	Composite video built in camera
HDSDIC	HD SDI camera
DynamicTalk	Built in DynamicTalk
CCUSB	USB connector on cover plate
CC2USB	2 USB connectors on cover plate
CCUSBPower	USB power on cover plate

Specifications subject to change without previous notice. Albiral is a registered brand by ALBIRAL DISPLAY SOLUTIONS SL