

FULL HD 18.47" metal cabinet monitor. Wall mount monitor**Ref: 19WMHD****GENERAL SPECIFICATIONS**

LCD type	FULL HD 18.47" TFT Active Matrix. LED backlight
Cabinet	Powder coated. Wall mount monitor
Controls (*)	Digital

DISPLAY

Brightness	400cd/m2
Contrast ratio	1500:1
Resolution (dots)	1920(h) x 1080(v)
Pixel	0.213(h) x 0.213(v) mm
Viewing angle	85°/85°(u/d), 85°/85°(l/r)
Viewing area	408.96(h) x 230.04(v) mm
LED life time	50,000 hrs

OTHER

Response time	Tr+Tf 35 ms
Temperature	Operating +0°C ~ +40°C, Storage -20°C ~ +60°C

INPUTS & OUTPUTS (*)

Input signal	DVI-I (1 input) - HDCP Compliant DVI-D (1 input) - HDCP Compliant
--------------	--

ELECTRICAL

External power supply	100-240 Vac, 47/63Hz, 12Vdc
Power consumption	80 W

OPTIONS

PC	Built in industrial PC
WF	Wi-fi network for PC
MPEG	Built in mpeg player. CF player, MPEG1, MPEG2, MPEG4, (PAL/NTSC)
TS190HD	Touch screen
PG19 wide (**)	Protection polycarbonate

Specifications subject to change without previous notice. Albiral is a registered brand by ALBIRAL DISPLAY SOLUTIONS SL

(*) Not available with PC option

(**) Not available with touch screen option