

HS15 Headset



Description

After decades of experience in the field of conferencing, the HS15 is the apex of Televic's expertise in headsets. A sleek design paired with secure, high-quality audio, creates a perfect headset with excellent sound quality and an omnidirectional microphone. The HS15's optimal adjustment and lightweight design allows hours of use. After the conference, a simple hygienic tissue will prepare the unit for the next user, without the need to exchange expensive foam cushions. It's flexible enough to achieve different wearing positions. Finally, the cable is very soft and TPU covered to reduce the structure-borne noise.

- Omnidirectional condenser microphone

- Outstanding sound quality
- Single 3.5 mm jack

Specifications

Mechanical	
Cable diameter	ø 2.5 mm
Jack	ø 3.5 mm stereo, right-
	angled
Ear caps diameter	ø 53 mm
Ear caps adjustment	± 10° in each direction
(via gimbal joint)	
Ear pads contact	2.2 N
pressure	
Adjustment range	63 mm per side
for head size	
Electrical	
Acoustic	40 mm speaker
Impedance	32 Ω
Sensitivity	98 ±3 dB SPL/mW
	(@ 32 Ω)
THD @ nominal level	< 1% (@ 1 kHz @ 1 mW)
Frequency Range	20-20,000 Hz

All information copyright **Televic Conference**, 2015. Version 1.0, October 2015

Leo Bekaertlaan 1 · 8870 Izegem · Belgium Tel. +32 51 30 30 45 Fax +32 51 31 06 70 E-mail: conference@televic.com Web: <u>http://www.televic-conference.com</u> *Televic reserves the right to change this document without notice.*

Features

- Wide frequency range
- Ultra lightweight
- Wide adjustment range
- Low impedance technology
- Integrated clip on front panel
- The headband is made of soft TPE material